

SEAT DECAL (SD-001) INSTALLATION INSTRUCTIONS

©2009 3R1 Enterprises. All rights reserved



1: Determine where the decal is to be placed.
(**HINT:** Trim the paper backing very close to the sides, top & bottom of the decal. (**FIG 1**))



Fig. 1



Fig.2

Place the decal where you want it and use a dry erase marker to make alignment marks on the seat. (**Fig 2**) (This will help you locate the decal once the backing has been peeled off.)

2: Make sure the seat is clean and free of dust.

3: Gently peel the decal off the paper backing, holding it carefully by both pieces. (**Fig 3**)



Fig. 3

4: Carefully place the decal against the seat in the following manner. Use the method most comfortable for you.

- a. Place the bottom edge of the decal on the seat and use a small dry cloth wrapped over your finger to press the decal solidly onto the seat as you roll out the upper portion of the decal down onto the seat. Take care to remove all air bubbles as you wipe back and forth across the decal. **(Fig 4)**




Fig 4

- b. Place one side edge of the decal on the seat and use a small dry cloth wrapped over your finger to press the decal solidly onto the seat as you roll out the decal sideways onto the seat. Take care to remove all air bubbles as you wipe up and down on the decal. **(Fig 5)**




Fig. 5

- c. Hold both edges of the decal up, so as to have the center of the decal hanging down. Lower the center of the decal onto the seat and slowly lower both sides onto the seat. Once the decal is fully on the seat, use a dry cloth over your finger to press the decal firmly onto the seat while making sure that no air bubbles are trapped under the decal. **(HINT: Press the decal down, moving from the center outward, to help bubbles escape.) (Fig 6)**



Fig. 6